

BMMB

Value IP Camera



BMMBKL500

- Value IP Bullet
- 1/2.8" SONY Starvis Back-illuminated CMOS sensor
- H.265+ /H.265/H.264+ /H.264 Compression Method
- 3.6mm Fixed Lens
- IR Distance 40M Max.
- With Internal POE

www.longse.com

Data Subject To Change Without Notice

Longse

SPECIFICATION	
Model NO.	BMMBKL500
Camera	
Image Sensor	1/2.8" SONY Starvis Back-Illuminated CMOS sensor
Resolution	5MP
Effective Pixels	2614 (H) * 1964 (V)
Compression	H.264(H.265)/H.264/H.265
Audio Compression	G711A/U
TV System	PAL/NTSC
Electronic Shutter Time	Auto: 1/3-1/100000sec
Minimum Illumination	Color: 0.006 Lux @ (F1.6, AGC ON)A/W: 0 lux with IR
S/N Ratio	>52dB
Scanning System	Progressive
Video Output	Network
Reset Button	Optional
Lens	
Focal Length & FOV	2.8 mm, horizontal FOV 107°, vertical FOV 57°, diagonal FOV 128° 3.6 mm, horizontal FOV 88°, vertical FOV 44°, diagonal FOV 105° 6 mm, horizontal FOV 54°, vertical FOV 28°, diagonal FOV 63°
Lens Type	Fixed focal lens, 2.8, 3.6, and 6 mm optional
Focus Control	Fixed
Aperture	F1.6
Pixels	5MP
Night Vision	
Infrared LED	42x x 4PCS
Infrared Distance	40M
IR Status	Auto Control
IR Power On	Smart, Manual & Timed mode
Network	
Ethernet	10-45 (10/100Base-T)
Wireless	N/A
Protocol	TCP/IP, IPv6, iV6, ICMP, HTTP, HTTPS, FTP, DHCP, DNS, DDNS, RTP, RTSP, RTCP, RTP/RTSP, NTP, SMTP, UDP, SNMP, QoS, 802.1x
ONVIF	Support ONVIF 5.12(Profile S/T/G)
P2P	YES
POE	Optional External, Support IEEE 802.3af
Video Delay	0.3s (Within the Lan)
Main Stream 1	2592*1944@30fps
Main Stream 2	2560*1440@30fps
Main Stream 3	1920*1080@30fps 1280*720@30fps
Sub-Stream 1	1280*720@30fps
Sub-Stream 2	720*480@30fps
Sub-Stream 3	N/A
Tri Stream	N/A
IE Browser	IE9-11, Google Chrome, Firefox, Mac Safari
Smart Phone	iPhone, Android
AI Function	
Intelligent Analysis	Intrusion Detection, Line Cross Detection, Loiter Detection, People Gather Detection (based on human detection), Motion detection based on human detection
Camera Features	
Day/Night	Color/ B&W (IR-CUT)
Image Config	Saturation/Brightness/Contrast /Sharpness, Mirror, 3D NR, White Balance, Flicker Control, Video Tampering, ILC
Full Color	N/A
Corridor Pattern	Support
Defog Mode	N/A
ROI	Support
WLC	Support
WDR	120dB
Motion Detection	Support (support enable the detection based on human movement only)
Privacy Masking	3 Rectangular Zone
Recording Mode	NVR/CMS/Web
Language	Chinese Simplified, Chinese Traditional, English, Bulgarian, Polish, Arabic, German, Russian, French, Korean, Portuguese, Japanese, Turkish, Spanish, Hebrew, Italian, Nederlands, Czech, Vietnamese
Interface	
Audio	Optional 1 Built-In MIC
Alarm	N/A
SD Card Slot	Optional Internal, Support Max 512GB
RS485	N/A
General	
Housing	Cover: Plastic Main Body: Metal, IP67
Anti-cut Bracket	NO
IR Cut Filter	YES
Operation Temperature	-20°C ~ +60°C RH95% Max
Storage Temperature	-20°C ~ +60°C RH95% Max
Power Source	DC12V±10%, 950mA
Dimension	268(W) x 95(H) x 88(D)mm
Weight	1.5kgs

www.longse.com


Data Subject To Change Without Notice

Longse

Technical Specifications

Model	BMMB
Material	Aluminum & SECC & PC
Dimension(WxHxD)	95 x 88 x 268 mm
Weight	1.50kg
Color	White
Operating Temperature	-20°C ~ +60°C
Humidity	< 95% RH
Junction Box	B320

Dimensions (mm)



www.longse.com

Data Subject To Change Without Notice